

AliveDx

MOSAIQ[®]



TECHNICAL SPECIFICATIONS

AliveDx



MosaiQ Instrument
Ref number: 126001

- **Walkaway time:** over 7 hours
 - **Graphical User Interface:** Intuitive design ensuring users can effortlessly navigate with minimal clicks
 - **Multiplex testing:** 2 independent wells per microarray with simultaneous testing of multiple analytes supported by embedded internal calibration and controls
 - **Time to result:** First result <1h with subsequent results delivered every 42 seconds
 - **Loading capacity:** 1,000 Microarrays
 - **Test throughput:** 85 samples per hour
 - **Sample volume:** From 10 µl to 20 µl per panel
 - **Resource Management:** Fully automated, consumption expiration with on-board stability managed by RFID* Read/Write
 - **Alarm system:** Visual and audible system
 - **Bidirectional connection:** ASTM, Query mode
- *RFID = Radio frequency identification

Dimensions and weight

WIDTH: Closed: 174 cm (68.51 in)

DEPTH: Closed: 90 cm (35.44 in)

HEIGHT: 166 cm (65.36 in)

WEIGHT: 285 kg (628.3 lb)

Space requirement

WIDTH: 374 cm (147.25 in)

DEPTH: 200 cm (78.74 in)

HEIGHT: 166 cm (65.36 in)

Power requirement

VOLTAGE: 100 V – 240 V

FREQUENCY: 50 – 60 Hz

INPUT CURRENT: 2.5 – 6A

POWER: Idle power usage: 0.3 kWh
 Running power usage: 0.6 kWh

MEAN: 400 W (600 W max.)

FUSES: Primary T6.3 AH/250 VAC

Computer and connections

PROCESSOR: Intel Core i5

MEMORY (RAM): 16 GB DDR4

HARD DISK: 1 TB

PORTS: 2 LAN port – USB Ports

MONITOR: 43.9 cm (17.3 in) touch screen

OPERATING SYSTEM: Microsoft® Windows 10
 Enterprise LTSC (US English)

Environmental conditions

TEMPERATURE: Operating: 18 – 30 °C (64.4 – 86°F)
 Storage: 5 – 40 °C (41 – 104 °F)
 Transport: -10 – 55 °C (14 – 131 °F)

HUMIDITY: Operating: 15 – 80% non-condensing
 Storage: 10 – 85% non-condensing
 Transport: 10 – 90% non-condensing

POLLUTION DEGREE: 2

SUNLIGHT: No direct sunlight

ALTITUDE: Up to 2,000 m (6562 ft) above mean sea level

NOISE: 47 dBA at 100 cm (39.4 in) around
 59 dBA at 25 cm (9.8 in) around

HEAT OUTPUT: 1150 BTU/h

Fluidics

2 x 10 L system liquids or direct plumbing connection
 2 x 10 L liquid waste containers or direct drain connection

Contact Us <https://alivedx.com/mosaiq-inquiry/>



© AliveDx Suisse SA, 2024. AliveDx, the AliveDx logo and MosaiQ, are trademarks or registered trademarks of AliveDx group companies in various jurisdictions. Menus and capabilities are subject to change. Not all methods may be available in all territories. Subject to regulatory clearance.